Steps to add network printer on Mac OSX:

- 1. Make sure you have HP LaserJet Mac OS X driver installed. You can find it <u>here</u>. The one successfully tested is the one at the bottom "HP LaserJet Macintosh OS X Binary Print Driver Installer"
- Make sure you have access to your CSE samba directory by visiting it in your Finder. You can do this by going to Finder->Go->Connect to Server and then paste it the samba URL("smb://samba.cse.msu.edu/<your_NetID_here>") with your NetID put into the right place.

3. Go to Settings -> Printers & Scanners

○ ○ ○	Printers & Scanners	Q
	No printers are availa Click Add (+) to set up a	ble. printer.
	Default printer: Last Printer Used Default paper size: US Letter	÷ ?

4. Click "+" button on bottom left

000		Add		
	🙆 🚔 👘	Q		
Default Fax	IP Windows		Search	
Name			the Minut	
Name			≜ Kinû	
Name:	No Selection			
Location:	No Selection			
Use:				\$
				Add

5. If you dont see a "Advanced" toolbar item as in the above screenshot, right click in a empty area in the toolbar and hit "Customize Toolbar"

Default Fax IP Windows Q	
Delaute lax in Windows Scalen	\supset
Drag your favorite items into the toolbar	_
Windows Advanced IP Default Fax Search Space Flexible	• Space
or drag the default set into the toolbar.	
Default Fax IP Windows Search	\supset
Show Icon and Text 💠 🗌 Use small size 🛛 🖸	one
Add	

6. Drag "Advanced" into toolbar and hit "Done" to see a window like this.

00	Add	1	
efault Fax	IP Windows Advanced	(Q. Sear	ch
Name		▲ Kind	
Name:	No Selection		
Location:	No Selection		
Use:			*

7. Hit Advanced, it will show "Searching for printers..." for a few seconds followed by a window which looks like this.

000	Add	
Default Fax	IP Windows Advanced Search	\supset
Type:	Fax	\$
Device:	Another Device	\$
URL:	fax://	
Name	:	
Location		
Use	: Choose a Driver	\$
	Add	4

Select "Windows printer via spoolss" and change the rest of the options as per the printer you are trying to connect to. To select the right driver for the printer, Hit "Choose a Driver..." -> "Select software..." -> Select the right printer driver. For eg. you would want to select "HP LaserJet 4350" to connect to the creek printer in 3320 EB.

00	0	Add	
Defau	ult Fax	IP Windows Advanced Search	
_			
	Type:	Windows printer via spoolss	\$
	Device:	Another Device	\$
	URL:	smb://samba.cse.msu.edu/creek	
	Name	creek	
	Location	:	
	Use	: HP LaserJet 4350	\$
			Add
			Add

9. It will ask you to further setup a few more options as here.

000	Add	
Default Fax	IP Windows Advanced Search	\supset
c	Setting up 'creek' Make sure your printer's options are accurately shown here so you can take full advantage of them.	
	Optional Tray 3: Not Installed Optional Tray 4: Not Installed Optional Tray 5: Not Installed Duplow Unit	
Low street	Printer Hard Disk: Not Installed Accessory Output Bins: Not Installed	
Doe	Fit to Page: Prompt User ÷	

10. The default values should be ok so hitting "Ok" for most printers should work. After this step, it will connect to the printer and add it. You should now be able to see the printer added under "Printers & Scanners".

000	Printers & Scanners
Show All	Q
Printers Creek e Idle, Last Used	creek Open Print Queue Options & Supplies Location: Kind: HP LaserJet 4350 Status: Idle
+ -	Share this printer on the network Sharing Preferences
	Default printer: Last Printer Used Default paper size: US Letter ?

11. Thats it! Now you should be able to print to the newly added printer from any Mac OS X application. Happy printing!